
ESDIS PROJECT

EPGS Phase I Operation Concept Review NASA/Wallops Flight Facility



EOS Multi-Mission Operations Concept for Phase 2

4/17/97 - 4/18/97 [Corrected Version A, 4/29/97]

Angelita Kelly, Code 505, angie.kelly@gsfc.nasa.gov Alex Herz, Omitron, alex.herz@omitron.com

Purpose & Scope

- Provide a preliminary Phase II end-to-end EOS multi-mission operations concept to be considered during Phase 1 design.
 - EOS series-1 spacecraft (AM-1, PM-1, LALT-1, CHEM-1)
 - Other MTPE spacecraft (LANDSAT-7, EO-1) considered in EPGS loading and operations concept
 - Operations period through 2003
 - Assumes AM-1 has transitioned to EPGS
- Focus on spacecraft operations and science data acquisition
 - Science data processing operations not considered in detail

EOS Series-1 Mission Profiles

| Mission | Orbital Data Volume | Onboard Storage | Downlink | Orbit Design | Mission |
|------------|------------------------|-----------------|-----------------|-----------------------|---------|
| | volume | Capacity | Rates (bps) | Requirements | Period |
| | | | 150M (X-PB) | 705 km circular | |
| AM-1 | 110 Gbits | 160 Gbits | 512K (S-PB) | 98.2 inclination | 6/98 - |
| | | | 16K (S-RT) | 10:20 Descending Node | 6/04 |
| | | | 150M (X-PB) | 705 km circular | |
| PM-1 | 52 Gbits | 136 Gbits | 512K (S-PB) | 98.2 inclination | 12/00 - |
| 1 | | | 16K (S-RT) | 13:30 Ascending Node | 12/06 |
| | | | | 600 km circular | |
| LALT-1 | 7.5 Gbits/Day | 15 Gbits | 25M (X-PB) | 94.0 inclination | 7/01 - |
| | (compressed) | (TBD) | (TBD) | No nodal requirement | 7/06 |
| | | | 150M (X-PB) | 705 km circular | |
| CHEM-1 | 30.3 Gbits | 88 Gbits | 512K (S-PB) | 98.2 inclination | 12/02 - |
| 0112 | | | 16K (S-RT) | 13:45 Ascending Node | 12/08 |
| | Imaging: | | 150M (X-PB,RT) | 705km circular | |
| LANDSAT-7 | 378 Gbits | 378 Gbits | 256K (S-PB) | 98.2 inclination | 5/98- |
| EMIDS/II / | every 42 min. | | 1 or 4K (S-RT) | 10:00 Descending Node | 5/05 |
| | | | 105 Mbps (X-PB) | 705km circular | |
| EO-1 | 80 Gbits/Day | 40 Gbits | 1 Mbps (S-PB) | 98.2 inclination | 5/99 - |
| | | | . , , | 10:01 Descending Node | 5/00 |

Note 1: 2kbps nominal S-band uplink rate for all spacecraft

Note 2: EPGS does not provide sole support for Landsat-7 or EO-1 missions (Reference Slide 11 for dump support details)

Operations Overview

■ Flight ops based on AM-1 concept


- EOC is the focus of operations
 - Health & Safety monitoring for instruments & spacecraft
 - All mission planning, scheduling, and commanding
 - Ground System configuration & scheduling
 - Instrument Operations Teams (IOTs) provide instrument inputs via Instrument Support Toolkits (ISTs)

■ Relatively autonomous spacecraft

- Automatic safing modes & reconfigurations
- Stored command loads
- Onboard ACS control loop
- Automated onboard data collection and storage

Primary RF Link via EPGS

EOS Ops Concept Overview



04/29/97

EOS Ground System (EGS) Overview

■ Shared EGS Resources

- EOS Data & Operations System (EDOS)
- EOS Operations Center (EOC)
- EOSDIS Backbone Network (EBnet)
- EOS Polar Ground Stations (EPGS)
- NCC, TDRSS, FDD, SDVF (Institutional Resources)
- DAACs & Affiliated Data Centers (e.g., NOAA)

■ Flight-Specific Resources

- Flight-specific EOC databases, displays & tools
- Instrument-specific IST displays
- Spacecraft-specific simulators

Communications Overview

■ EOS Polar Ground Stations (EPGS)

- Ground stations in Alaska & Norway
- Provide all primary communications with EOS spacecraft
 - S-band command & telemetry
 - X-band high rate downlink
 - Combined coverage = 15 min./orbit/spacecraft (average)

■ WOTS provide backup S-band support

■ TDRSS provides 70%+ orbital coverage:

- Special operations coverage (orbit maneuver burns, etc.)
- Emergency low rate command and telemetry
- Nominal tracking & clock correlation
- Backup high-rate K-band science downlink (AM-1 only)

Daily Ground Station Coverage

Typical for 705km circular orbit @98.2º inclination: Applies to AM-1, PM-1, CHEM-1 [LALT-1 coverage is approximately 10% less due to lower altitude orbit (600km)]

| | Norway | Alaska | Overlap | Gap | Total |
|----------|--------|--------|---------|------|--------|
| Orbit 1 | 11:35 | 0 | 0 | 0 | 11:35 |
| Orbit 2 | 11:42 | 0 | 0 | 0 | 11:42 |
| Orbit 3 | 11:33 | 0 | 0 | 0 | 11:33 |
| Orbit 4 | 11:29 | 0 | 0 | 0 | 11:29 |
| Orbit 5 | 11:36 | 0 | 0 | 0 | 11:36 |
| Orbit 6 | 11:42 | 8:40 | 0:35 | 0 | 19:47 |
| Orbit 7 | 11:22 | 11:30 | 1:15 | 0 | 21:37 |
| Orbit 8 | 10:19 | 11:16 | 1:40 | 0 | 19:55 |
| Orbit 9 | 8:24 | 9:20 | 2:18 | 0 | 15:26 |
| Orbit 10 | 5:56 | 7:19 | 3:50 | 0 | 9:25 |
| Orbit 11 | 4:19 | 7:34 | 4:19 | 0 | 7:34 |
| Orbit 12 | 5:36 | 9:43 | 2:02 | 0 | 13:17 |
| Orbit 13 | 8:05 | 11:26 | 1:05 | 0 | 18:26 |
| Orbit 14 | 10:07 | 11:17 | 0:27 | 0 | 20:57 |
| Orbit 15 | 11:17 | 7:40 | 0:00 | 0:39 | 18:57 |
| Total | 145:02 | 95:45 | 17:31 | | 223:26 |
| Average | 9:40 | 9:34 | _ | _ | 14:53 |

Assumptions: 5⁰ minimum elevation and line-of-sight links (no spacecraft masking).

Total coverage per orbit adds coverage times for Alaska and Norway and subtracts any overlap.

Orbits with no Alaska coverage not included in Alaska average calculation. Alaska average for all orbits is 6:23.

Onboard Data Management

■ Solid State Recorder (SSR) Assumptions for EOS Series-1 Spacecraft

- At least 2-orbit capacity except for AM-1 (see table on next page)
- Partitioned for each instrument & spacecraft H/K
- Multiple Inputs, single output
- Simultaneous record/playback (including H/K except on AM-1)
- Data Position Pointers in X-band & S-band downlinks
- Write-protectable data
- Playback order managed by the Flight Operations Team

Data Volumes & Downlink Times (X-band dump time per orbit)

| | Data Volume (per orbit) | Downlink Rate | Downlink Time/Orbit | Recommended Dump Plan |
|-------------|----------------------------|------------------|------------------------|---------------------------|
| AM-1 | 110 Gbits | 150 Mbps | 12:13 | Every Contact (1-2/orbit) |
| PM-1 | 52 Gbits | 150 Mbps | 5:47 | Once per Orbit |
| LALT-1 | 0.5 Gbits | 25 Mbps | 0:20 | Once per Day ³ |
| CHEM-1 | 30.3 Gbits | 150 Mbps | 3:22 | Once per Orbit |
| LANDSAT-7 | 324 Gbits ¹ | 150 Mbps | 36:00 | See Note 2 |
| EO-1 | 5.33 Gbits | 105 Mbps | 00:51 | 4 Dumps/Day ³ |

Note 1: LANDSAT-7 data volume equals 36 minutes of imaging (42 minute recorder capacity)

Note 2: EPGS sites not prime for all LANDSAT-7 support. 4 passes per day requested for AGS, 1 pass for SGS...

Note 3: Dump plan requires greater than 2-orbit recorder capacity.

Note 4: EPGS now prime for EO-1 support. 4 passes per day requested..

EPGS Contact Scenario

■ Primary Ground Station

- S-band Telemetry
 - Real-time housekeeping data for duration of pass
 - Capability to dump playback housekeeping data
- Real-time S-band commands and command load uplinks
- X-band Dump
 - Playback housekeeping data followed by science data

■ Secondary Ground Station (on same orbit - if any)

- Extended S-band real-time telemetry if schedule allows
- Additional X-band playback time (if required)

■ Ground Station Control

- Ground station status monitored by the EOC during the pass
- Pre-pass interface checks performed by the EOC

EGS Data Routing

■ EPGS Ground Stations

- Acquire S-BD and X-BD downlinks
- Throughput S-BD downlinks to LZPF in real-time
- Forward X-BD dump data to LZPF post-pass

■ Real-Time S-band Telemetry

- Forwarded from EPGS to EOC in real-time
 - EPGS to LZPF
 - via satellite link from Norway (rate TBD)
 - via satellite or ground link from Alaska (rate TBD)
 - LZPF performs level zero processing
 - LZPF forwards data to EOC

EGS Data Routing (continued)

■ X-band dumps

- Recorded at the ground station during the pass
- Forwarded from EPGS site to LZPF post-pass
 - Via ground or satellite link (rate TBD)
 - Data forwarded in priority order
 - Housekeeping (supports health & safety analysis prior to next orbit)
 - Instrument science data in priority order
 - Order of forwarding determined by order of S/C playbacks
- LZPF forwards data to appropriate destination
 - VCID and APID processing
 - Housekeeping data to EOC (also to ASTER ICC for AM-1)
 - Level zero processed science data sets to appropriate DAAC

Science Data Quality Monitoring

- Phase 1 data quality monitoring is limited to EPGS sites (due to tape shipment of data)
- Phase 2 data quality monitoring can be performed at EPGS sites and/or EDOS LZPF (due to timely data transfers)
- Troubleshooting of poor quality science data is coordinated by the EOC

Ground Station Scheduling

- EOC determines ground station support schedule requirements for all EOS spacecraft.
 - Determined mainly by spacecraft orbit and coverage times
 - Also affected by data volumes, command activity, recorder capacity, data rates, and real-time monitoring requirements.
- EOC generates integrated EPGS schedule request for all EOS spacecraft
- EPGS scheduling process TBD

Commanding Operations

- All commanding performed by EOC
- S-band Command links available to each spacecraft each orbit via EPGS
- CCSDS Command Operations Procedure 1
- Real-time commanding for dump control and anomaly resolution
- Time-tagged command load uplinks for most nominal mission operations
- Command routing: FOS to EDOS to EPGS

Health & Safety Monitoring

Performed by EOC for spacecraft and all instruments

• Instruments may also be monitored via IST or Instrument Control Centers by Instrument Operations Teams (IOTs)

Housekeeping Data

- Processed at EOC (real-time and playback data)
- Playback data forwarded to EOC within 30 minutes of contact

Housekeeping Playbacks

- Nominally dumped via X-band
- S-band dump also available, but reduces time for X-band science dump

Flight Dynamics Support

■ Tracking data

- TDRSS tracking planned for AM-1(TONS), PM-1
- Use of EPGS tracking data to be analyzed by FDD
- Tracking by non-EPGS ground sites may also be available
- LALT-1 GPS may eliminate most tracking support needs
- Tracking data processed on FDD systems

■ Clock correlation via EPGS

- TDRS PN Epoch method planned for AM-1, PM-1
- EPGS clock correlation alternatives to be analyzed

■ FDD System at EOC generates all routine products:

• Planning aids, daily predicted orbit updates, acquisition data

Ground Station Contention (?)

- EPGS sites can support multiple missions
- EPGS loading analysis for Phase 2 in work (D. Elwell)
- EOS series-1 constellation design mandatory prior to PM-1 launch
 - Coordinated orbit design/maintenance alleviates ground station contention

EPGS to LZPF Bandwidth Contention (?)

- Data downlink per orbit period for all EOS series-1 spacecraft is 199.8 Gbits (maximum)
 - Equates to 74-minute transmission time @ 45Mbps (T3)
 - Based on a 100 minute EOS orbit period, 45Mbps EBnet bandwidth supports Phase 2 EOS mission requirements for timely data recovery
 - 74-minute transmission time assumes that all data goes to a single ground site and is transmitted over a single T3 line (worst case)
- Good constellation design is required to eliminate transmission delays
- If full T3 capacity is not available, there may be problems as transmission time approaches 100 minutes on single-site orbits

Spacecraft Implications

- Multi-mission operations concept impacts spacecraft design requirements, e.g.
 - Onboard recorder sizing
 - Downlink rates & formats
 - Spacecraft autonomy
 - Tracking systems
- EOS MOM coordinating with flight projects to ensure spacecraft designs are consistent with multi-mission operations concept

Next Steps

- Determine science data quality monitoring implementation
- Determine EPGS scheduling process
 - for EOS spacecraft
 - for non-EOS spacecraft (Landsat, etc.)
- Perform EOS series-1 constellation design
- Plan working meeting to generate EPGS multimission operations concept to support June 1997 EPGS Phase 2 architecture review

Acronym & Abbreviation List

| ACS | Attitude Control System | GSIF | Ground Station Interface Facility |
|--------------|---|-------|---|
| AI | Artificial Intelligence | H/K | Housekeeping |
| AIRS | Atmospheric Infrared Sounder | HSB | Humidity Sounder Brazil |
| AM | EOS AM Mission | ID | Indentifier or Identification |
| AMSR | Advanced Microwave Scanning Radiometer | IOT | Unstrument Operations Team |
| AMSU | Advanced Microwave Sounding Unit | IST | Instrument Support Toolkit |
| ASAP | As Soon As Possible | KBPS | Kilobits Per Second |
| ASTER | Advanced Spaceborne Thermal Emission and | KM | Kilometer |
| | Reflection Radiometer | LALT | EOS Laser Altimeter Mission |
| BAP | Baseline Activity Profile | LEO | Low Earth Orbit |
| BD | Band | LZPF | Level Zero Processing Facility |
| CAC | Command Activity Controller | MA | Multiple Access |
| CCSDS | Consultive Committee for Space Data Standards | MBPS | Megabits Per Second |
| CERES | Clouds & Earth's Radiant Energy System | MGA | Medium Gain Antenna |
| CHEM | EOS Chemistry Mission | MIN | Minutes |
| CMD | Command | MODIS | Moderate Resolution Imaging Spectromter |
| CMS | Command Management System | NCC | Network Control Center |
| CRC | Cyclic Redundancy Check | NOAA | National Oceanic & Atmospheric Administration |
| DAAC | Distributed Active Archive Center | PM | EOS PM Mission |
| EBNET | EOSDIS Backbone Network | PN | Pseudo-Random Noise |
| EDOS | EOS Data and Operations System | RF | Radio Frequency |
| EGS | EOS Ground System | RTCS | Relative Time Command Sequence |
| EOC | EOS Operations Center | RTN | Return |
| EOS | Earth Observing System | SDVF | SoftwareDevelopment & Verification Facility |
| EOSDIS | EOS Data and Information System | SSA | S-band Single Access |
| EPGS | EOS Polar Ground Stations | SSR | Solid State Recorder |
| FDD | Flight Dynamics Division | TBD | To Be Determined |
| FDIR | Failure Detection, Isolation, Recovery | TDRS | Tracking & Data Relay Satellite |
| FOS | Flight Operations System | TDRSS | Tracking & Data Relay Satellite System |
| FOT | Flight Operations Team | TLM | Telemetry |
| FS | Slight Software | TMON | Telemetry Monitor |
| FWD | Forward | TOO | Targets Of Opportunity |
| Gbit | Gigabit | WOTS | Wallops Orbital Tracking Station |
| | | | |

04/29/97